

4087-03

Zinc Rich Cold Galvanizing is highly resistant to all forms of corrosion. Through galvanic action, small scratches "heal" themselves. Perfect where factory galvanized finish is damaged in shipment, assembly, welding, etc. Blends well with hot-dip coating. Forms a zinc film that by electro-mechanical reaction literally fuses itself to iron, steel, and aluminum.

DIRECTIONS FOR USE:

Shake can for a full sixty (60) seconds after rattling of mixing ball begins. If application is to cover a large area, periodically shake can to insure uniform mixing of the contents. Surface to be sprayed should be clean and dry. Remove protective cap and point opening in spray nozzle towards surface to be sprayed. Holding can 10 to 12 inches from the surface using a sweeping motion, apply

in thin, even coats until surface is completely covered. After spraying, turn can upside down and spray until no more zinc is evident. This product is best applied at room temperature (70-80°F). Coating should be touch dry in 15 minutes. May be painted over after allowing approximately six hours to dry. Cures in 24 to 48 hours.

TYPICAL USES:

Rust-proofing all welds, air conditioning and heating ducts, sumps, iron, pipes, structural steel work and fan blades, chemical and oil refineries, farm equipment, sign equipment, and anywhere metal is subject to corrosion and rust. Does not contain pvc monomer. Metallic Coatings (MCP) Do Not Exceed 80% VOC or 1.90 MIR.



DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

PREVENTION: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapour. Use only outdoors or in a well-ventilated area.

RESPONSE: IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **IF INHALED:** remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

STORAGE: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Keep container tightly closed.

DISPOSAL: Dispose of container in accordance with local, regional, national and international regulations.

Contains (CAS#): Cadmium (7440-43-9), Copper (7440-50-8), Distillates (petroleum), light hydrotreated (64742-47-8), Lead (CAS 7439-92-1), Toluene (108-88-3), Zinc oxide (1314-13-2), Zinc, elemental (7440-66-6).




WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Made in the U.S.A.
 Manufactured for:
 Nu-Calgon
 2611 Schuetz Rd.
 St. Louis, MO 63043
 Customer Service: 800-554-5499
 Chemical Emergency: 800-424-9300
www.nucalgon.com
 (619) Calgon is a licensed trade name.

Zinc Rich

COLD GALVANIZING COMPOUND

Highly Resistant to Corrosion



**Perfect for Repairing
 Factory Galvanized Metal**

DANGER:

EXTREMELY
 FLAMMABLE.

CONTENTS UNDER
 PRESSURE.

KEEP OUT OF REACH
 OF CHILDREN.
 See back panel for
 additional precautionary
 statements.

**FOR PROFESSIONAL
 USE ONLY**

NET WT. 13 OZ. (368 GRAMS)