4120-05



Alka-Brite Plus

CONDENSER COIL CLEANER

High Foaming Cleaner and Brightener



Pushes Dirt Out of the Coil Cleans and Degreases Revitalizes Coil



FOR PROFESSIONAL USE ONLY

2.5 U.S. Gallons (9.46 Liters)

APPLICATION:

Outdoor air conditioning coils of aluminum or copper fin construction. For painted fin or microchannel coils, consider Tri-Pow' r^{\otimes} HD, Cal-Green, CalClean, or TriClean, or TriClean, and the construction of the construction.

DOES NOT CONTAIN ACID. DO NOT USE ON INDOOR COILS. NOT FOR INDOOR USE.

DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

- 1. Goggles, gloves and other protective garments should be worn when using this product. System must be shut off.
- 2. Apply only with one of the durable Nu-Calgon low pressure poly sprayers.
- 3. Prepare cleaning solution by mixing one part Alka-Brite[®] Plus with four parts of water. Add the water to the sprayer first, then add the Alka-Brite Plus.
- 4. Spray Alka-Brite Plus onto dirty coils and allow it to remain in contact with the dirty surfaces for 5-10 minutes.

- 5. Rinse thoroughly with water, ensure cleaning solution is removed from the coil.
- Apply Cal-Shield[®] as a coil protectant and return system to service.
- 7. Rinse out sprayer, spraying wand, and nozzle.
- 8. When the Alka-Brite Plus container is empty, rinse, replace cap and dispose of properly.

NOTE: For maximum results, do not use Alka-Brite Plus undiluted or any stronger than one part cleaner to three parts water.

AFFECT ON ROOFING MATERIAL: Depending on its composition and condition, the color and finish of roofing material can be affected by coil cleaners (e.g. discoloration or tarnishing). It is recommended that the coil cleaner be tested on a small area of the roof prior to cleaning, particularly galvanizing or standing seam metal roofs. Do not use on aluminum or aluminum-coated surfaces.

RUBBER ROOFS: In general, the product is safe on rubber except where the rubber roof is impregnated with aluminum chips (i.e. modified bitumen roof); do not use on rubber roofs that contain aluminum. In these circumstances, use CalClean[®], Cal-Green[™], Green Clean or Tri-Pow′r[®] HD - first evaluate in a small test area.



DANGER

Causes severe skin burns and eye damage.

PREVENTION: Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection.

RESPONSE: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF INHALED: remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. KEEP OUT OF REACH OF CHILDREN.

STORAGE: Store locked up.

DISPOSAL: Dispose of container in accordance with local, regional, national and international regulations.

Contains (CAS#): Water (7732-18-5), Sodium Hydroxide (1310-73-2), Carboxylate Sodium Salt (Proprietary), Plant Derived Surfactant (Proprietary), Plant Derived Surfactant (Proprietary), Colorants. For more ingredient information, visit www.nucalgon.com. 800-554-5499.













Nu-Calgon 2611 Schuetz Rd. St. Louis, MO 63043 Customer Service: 800-554-5499 Chemical Emergency: 800-424-9300 www.nucalgon.com (1220) Calgon is a licensed trade name.