APPLICATION:

This Alka-Brite®+ 4X container provides equal performance to one gallon of Alka-Brite®+ (4:1 ratio) when a smaller size is desired. For outdoor air cooled coils of aluminum fin/copper tube construction. For painted fin or microchannel coils, consider Tri-Pow'r® HD 4X with the Clean Connect Spraver (4773-0) or Cal-Green 4x.

DO NOT USE ON INDOOR COILS. FOR OUTDOOR USE ONLY. DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

- 1. Goggles, gloves and other protective garments should be worn when using this product. System must be shut off.
- 2. Connect hose assembly to Clean Connect Sprayer. If Probe connector is used, tighten with wrenches to Nu-Calgon Probe (4774-1) for the first time, then attach to spraver.
- 3. Connect Clean Connect Sprayer to bottle, keep bottle cap.
- 4. Toggle to clean mode on sprayer and depress handle to spray diluted solution onto dirty condenser coil. Allow it to remain in contact on the dirty surface for 5-10 minutes.

5. Toggle to rinse on sprayer and rinse coil thoroughly with water. 6. Apply Cal-Shield® as a coil protectant and return system to service. When the Alka-Brite®+ 4X container is empty, replace cap and dispose of properly or if contents remain recap bottle for another job. Nu-Calgon



2611 Schuetz Road St. Louis, M0 63043 Customer Service: 800-554-5499 Chemical Emergency: 800-424-9300 www.nucalgon.con 20) Calgon is a licensed trade name



CONCENTRATE COIL CLEANER

.......... Use With Clean Connect Sprayer

High Foaming Cleaner and Brightener

Cleans and Degreases

Equal to One Gallon of Alka-Brite®+



Clean Connect Spraver Adapts to Nu-Calgon Probe P/N: 4773-0

Features:

✓ Concentrate quart = gallon traditional Alka-Brite+ (4:1 ratio)

P/N: 4774-1

- ✓ Takes less space on truck
- ✓ Easier to carry around
- ✓ Cleaner connecting no more pouring or spilling
- ✓ Use what is needed simply cap bottle for next iob
- ✓ Dilution orifice in bottle less likely for spraver to clog
- ✓ Easier to ship to job sites

AFFECT ON ROOFING MATERIAL: Depending on its composition and condition, the color and finish of roofing material can be affected by coil cleaners (e.g. discoloration or tarnishing). It is recommended that the coil cleaner be tested on a small area of the roof prior to cleaning, particularly galvanizing or standing seam metal roofs. Do not use on aluminum or aluminum-coated surfaces

RUBBER ROOFS: In general, the product is safe on rubber except where the rubber roof is impregnated with aluminum chips (i.e. modified bitumen roof); do not use on rubber roofs that contain aluminum. In these circumstances, use CalClean®, Cal-Green™, Green Clean or Tri-Pow'r® HD - first evaluate in a small test area

<u>v</u> %

DANGER

May be corrosive to metals. Causes severe skin burns and eve damage.

PREVENTION: Keep only in original packaging. Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves. protective clothing, eye protection and face protection. RESPONSE: Absorb spillage to prevent material-damage. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF INHALED: remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF IN EYES: Binse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. STORAGE: Store locked up. Store in a corrosion resistant container with a resistant inner liner DISPOSAL: Dispose of container in accordance with local, regional, national and international regulations. KEEP OUT OF REACH OF CHILDREN Contains (CAS#): Water (7732-18-5), Sodium Hydroxide (1310-73-2), Carboxylate Sodium Salt (Proprietary), Caprylyl/Capryl Glucoside (68515-73-1), D-Glucopyranose, Oligomeric, C10-C16-Alkyl Glycosides (110615-47-9). Colorants. For more ingredient information, visit www. nucalgon.com. 800-554-5499.