Foam-Brite® is a non-acidic, alkaline-based cleaner and brightener containing a unique chelant/surfactant formulated to quickly penetrate and remove greasy soils and oxidation. Its maximum foaming formula penetrates and lifts greasy soils out of the coil.

APPLICATION:

Outdoor air conditioning coils of aluminum or copper fin construction. For painted fin or microchannel coils, consider Tri-Pow'r[®] HD, Tri-Pow'r HD[®] 4x, Cal-Green™, Cal-Green[™] 4x, CalClean[™] or TriClean 2x[™].

DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

- 1. Goggles, gloves, and other protective garments should be worn when using this product. System must be shut off.
- 2. Apply using any of the Nu-Calgon sprayers or other durable low pressure plastic sprayer.
- 3. Prepare Foam-Brite solution by mixing one part Foam-Brite with four parts of water. Add the water to the spraver first, then add the Foam-Brite.
- 4. Spray Foam-Brite solution onto dirty condenser coils and allow it to remain in contact with the dirty surfaces for 5-10 minutes.
- 5. Rinse thoroughly with water, ensure cleaning solution is removed from the coil.
- 6. Apply Cal-Shield[®] as a coil protectant and return system to service.

7. Rinse out sprayer, spraying wand and nozzle.

8. When the Foam-Brite container is empty, rinse, replace cap and dispose of properly.

DOES NOT CONTAIN ACID.

DO NOT USE ON INDOOR COILS. NOT FOR INDOOR USE

DILUTION CHART		
Outdoor Coil - Light Soil	1 part Foam-Brite : 8 parts water	P. COFGRADA
Outdoor Coil - Medium Soil	1 part Foam-Brite : 6 parts water	
Outdoor Coil - Heavy Soil	1 part Foam-Brite : 4 parts water	
		1000

4178-01

CONDENSER COIL CLEANER

Foam-Brile

Maximum Foaming Coil Cleaner and Brightener

> **Removes the Toughest Deposits Excellent Degreasing** Capability

(NSF)

Nonfood Compound

Program Listed P1

Nu-Calgon

FOR PROFESSIONAL USE ONLY Registration # 146046 AFFECT ON ROOFING MATERIAL: Depending on its composition and condition, the color and finish of roofing material can be affected by coil cleaners (e.g. discoloration or tarnishing). It is recommended that the coil cleaner be tested on a small area of the roof prior to cleaning, particularly galvanizing or standing seam metal roofs. Do not use on aluminum or aluminum-coated surfaces. **RUBBER ROOFS:** In general, the product is safe on rubber except where the rubber roof is impregnated with aluminum chips (i.e. modified bitumen roof); do not use on rubber roofs that contain aluminum. In these circumstances, use CalClean, Cal-Green, Green Clean or Tri-Pow'r HD - first evaluate in a small test area.



PREVENTION: Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves, protective clothing, eve protection and face protection. RESPONSE: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. **IF INHALED:** remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. Specific treatment (see information on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. KEEP OUT OF REACH OF CHILDREN. STORAGE: Store locked up. **DISPOSAL:** Dispose of container in accordance with local, regional, national and international regulations. Contains: Sodium Hodroxide (CAS# 1310-73-2). Water, Carboxylate Sodium Salt, Plant Derived Surfactant, Sodium Hydroxide, Reactive Yellow.







Customer Service: 800-554-5499 • Chemical Emergency: 800-424-9300 www.nucalgon.com • (0620) Calgon is a licensed trade name.

55 U.S. Gallons (208.18 Liters)