.375 inches glue flap

8.625 inches

This high performance aerosol has excellent solvency and blasting spray to powerfully separate undesirable materials from the surface, offering maximum cleaning of finned coils.

DIRECTIONS FOR USE: This product must be used in accordance to the following directions by HVACR professionals only.

- 1. Spray in well ventilated area.
- 2. Be certain there is nothing behind coil that could be hit by spray. Place cloth or other protection under coil.
- 3. Spray entire coil surface, allowing blast pressure as well as cleaner to work. Thoroughly saturate entire surface with product.
- DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. May be fatal if swallowed and enters airwavs.

PREVENTION: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection and face protection. Wear protective gloves.

RESPONSE: IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF INHALED: remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked

up. DISPOSAL: Dispose of container in accordance with local, regional, national and international regulations.

KEEP OUT OF REACH OF CHILDREN

CONTAINS (CAS#): Acetone (67-64-1), n-Heptane (142-82-5), Nitrogen (7727-37-9), D-Limonene (5989-27-5), 2,6-Octadienal, 3,7-dimethyl- (5392-40-5). For more ingredient information visit www.nucalgon.com.





Made in the U.S.A. Manufactured for: Nu-Calgon 2611 Schuetz Rd. St. Louis, MO 63043 Customer Service: 800-554-5499 Chemical Emergency: 800-424-9300 www.nucalgon.com (0523) Calgon is a licensed trade name.

4. Allow the product to flush soils from the coil onto the cloth. Once the coil surface is dry by evaporation, remove cloth.

5. Wait a minimum of 5 minutes before equipment start-up.

IMPORTANT: The product may affect certain plastics, including those used in newer model drain pans, and painted or wax finishes. Do not allow product to remain in contact with these materials. Wipe immediately with an absorbent media such as paper or cloth towels.

4132-21

a Basti

CONDENSER COIL CLEANER

No Rinse Required

Nu-Calgon

High Solvency Cleaning Power Works Great on All Soils Pressure Blasting Spray **Leaves No Residue** Nonconductive



Pleasant **Citrus Scent**

DANGER: EXTREMELY FLAMMABLE. MAY BE FATAL IF SWALLOWED. SKIN IRRITANT. CONTENTS

UNDER

PRESSURE.

KEEP OUT OF REACH OF CHILDREN. See back panel for additional precautionary statements.

FOR PROFESSIONAL **USE ONLY**

13.6 OZ. 385 GRAMS